

## Rough-Tex Diving Platform Surface

### Specification Sheet

*Springboards and More*, a division of DIVE Cincinnati, Inc. is the leading supplier of Rough-Tex Diving Platform Surface in the United States. Rough-Tex Diving Platform Surface is available in four styles: 2-Ply Black; 3-Ply Black; 2-Ply Tan; 3-Ply Tan and it is available in any width up to six feet across.

#### **THE COVER COMPOUND SHALL BE:**

BLACK: General Purpose SBR Rubber  
TAN: Pure Gum Rubber

#### **THE CARCASS SHALL BE:**

2-Ply: Treated All Synthetic Fabric x Bare Bottom – 160 Pound Tension Rating  
3-Ply: Black Cotton / Polyester Blend x Friction Bottom – 90 Pound Tension Rating  
3-Ply: Tan Treated All Synthetic Fabric x Bare Bottom – 225 Pound Tension Rating

#### **OVERALL THICKNESS:**

2 Ply: 17/64"  
3 Ply: 9/32"

#### **WEIGHT (P.I.W.):**

*To determine approximate weight, multiply width (in inches) x P.I.W. x length (in feet)*

2 Ply 0.09  
3 Ply 0.12

#### **TEMPERATURE RATING:**

0 Degrees Fahrenheit – 200 Degrees Fahrenheit

#### **RECOMMENDED METHOD OF ATTACHMENT:**

Use a good contact cement such as 3M 1300 or 1357  
Must have a good clean surface with no paint.  
Scuff the surface of the concrete before gluing to gain extra surface area to cement.  
Use an edge-sealing compound (to seal the edges)

Another good attachment product is Mondo PU100 2-part urethane adhesive.