

Installation Instructions Australian Folding Trampoline

With String Bed

Caution!

Any activity involving motion or height creates the possibility of catastrophic injuries including paralysis and even death. This equipment is intended for use ONLY by properly trained and qualified under supervised conditions. Use without proper supervision, or abuse, could be DANGEROUS and should NOT be undertaken or permitted.

Before use KNOW YOUR OWN LIMITATIONS and the limitations of this equipment. If in doubt, always consult your instructor.

Always inspect for loose fittings or damage and test stability before each use.

NOTE: MAT IS NOT TO BE LEFT IN TRAMPOLINE WHEN TRANSPORTED. SUPPLIER WILL NOT TAKE RESPONSIBILITY FOR DAMAGE OR MISUSE OF THESE MATS.

On Receipt: Check that all parts have been delivered in good order.

- 1 – Frame
- 2 – Roller Trolleys
- 1 – Mat
- 112 – 10” Jumbo Springs for Jumbo Model, 98 – 10” Jumbo Springs for Standard
- 1 – Set Safety Pads
- 2 – Spring Hooks

When signing for delivery, transport docket must be noted with any damages or shortages before service leaves your location.

Installation:

For safety and ease of installation, two people at least are required.

Remove the wrapping from the trolleys.

Note that on the side frame of the trampoline, the sockets, which accept the head of the trolleys, are off center. In relation to the trolley sockets, the trampoline has a long and short end.

Stand the folded frame upright on the top frame hinges so that the short end is uppermost.

Lift one side of the folded trampoline and insert the head of a trolley into the socket. Repeat for other side.

Note: The tee hook on the trolleys must be on the same side of the folded trampoline as the safety chains.

Untie or cut the twine securing the folded trampoline.

Note: In this position, the folded trampoline hangs on the trolleys and the leg hinged from the top hangs down over the leg hinged from the bottom and thus keeps it from swinging out. The same applies to the end frame - the top one is over the bottom one.

With one person standing adjacent to each trolley, lift the leg hinged from the top outward, tilt the folded trampoline so that the leg hinged from the bottom can be lowered to the floor and then both legs can be hinged fully out until the safety chains are taut.

Connect the inner stays on the legs into their sockets and place the safety links over the pins to prevent these stays working out of their sockets.

Alternately, lift each side and remove the trolleys.

Fold the end frames up and over and slowly lower to the horizontal position. (If the frame is dropped, the hinges can be damaged.)

Remove all the wrapping from the frame.

Connect the end stays into their sockets.

The Mat can now be fitted to the frame.

Lay out the Mat inside the frame with the markings upward.

Using a spring, attach the springs.

Warning! CONNECTING ALL THE SPRINGS ON ONE SIDE THEN ATTEMPTING TO PUT THE SPRINGS ON THE OTHER SIDE WILL ONLY RESULT IN STRETCHED SPRINGS!

First attach each corner spring on the side of the Mat.

Then the springs adjacent to the corner ones just attached, but on the end of the Mat.

Then, with one person at each side, work down each side connecting the springs opposite each other. Repeat, connecting the springs at each end alternately.

Attach the safety pads and the trampoline is ready for use.

TO FOLD:

Remove safety pads.

(If operators are not experienced, unhook springs alternately from ends of mat so no springs are attached to end frames.)

Lift one side and insert trolley. Repeat for other side.

Kick out the bottom connection of the end stays.

On the long end, fold over the end frame and rest on the center side frame.